

蝶阀 气动
Butterfly valve

K4  PN E

PO-NC¹
PO-NO²
PO-DA³

- 阳极电解铝外壳佩环氧
- 树脂粉末涂层端盖
- 任意位置安装
- 旋转角: 90 °, +/- 10 °
- 整体式可视阀位指示

- 附件
- 限位开关
 - 电磁先导阀

- Aluminium anodised body
- Aluminium epoxy powder coated end caps
- Any installation position
- Rotation angle 90°, +/- 10°
- Integrated optical position indication

- Accessories
- Limit switch box
 - Solenoid valve



- 1 单作用：常闭
Single acting: failsafe close
- 2 单作用：常开
Single acting: failsafe open
- 3 双作用
Double acting

		密封	Seals	尺寸	Dimensions	PN	连接方式	Connections
材料 Models	PVC	EPDM, FPM		DN65/d7 5/2½"-DN200/d22 5/8"		10	法兰连接	flange (ANSI, DIN, JIS)
	PP	EPDM, FPM		DN65/d7 5/2½"-DN200/d22 5/8"		10		
	PVDF	EPDM, FPM		DN65/d7 5/2½"-DN200/d22 5/8"		10		

		d	DN	G	W	J	K	D	C	Z	S	R	P	h	F	A	B	N	M	H
外型尺寸 Dimensions	UT-25 SR	75	65	2,5"	90	19	127-145	65	133	46	55	25	7	100	232	239	96	63	43	353
	UT-30 SR	90	80	3"	45	19	146-160	80	176	49	70	30	9	100	239	230	113	70	52	382
	UT-35 SR	110	100	4"	45	19	175-190,5	100	206	56	85	35	9	115	269	246	138	87,5	65,5	412
	UT-40SR	140	125	5"	45	23	209,5-216	125	234,5	64	100	45	9	130	303,5	290	138	87,5	65,5	499,5
	UT-45 SR	160	150	6"	45	23	234,5-241,5	150	261	70	110	45	9	147,5	333	351	151	92	73	529
	UT-50 SR	225	200	8"	45	23	290-298,5	200	314	71	145	40	9	175	395	361	185	114	91	591
	UT-17 DA	75	65	2,5"	90	19	127-145	65	133	46	55	25	7	100	232	197	85	48	35	353
	UT-20 DA	90	80	3"	45	19	146-160	80	176	49	70	30	9	100	239	177	96	60	43	382
	UT-25 DA	110	100	4"	45	19	175-190,5	100	206	56	85	35	9	115	269	239	96	63	43	412
	UT-30 DA	140	125	5"	45	23	209,5-216	125	234,5	64	100	45	9	130	303,5	230	113	70	52	465,5
	UT-35 DA	160	150	6"	45	23	234,5-241,5	150	261	70	110	45	9	147,5	333	246	138	87,5	65,5	529
	UT-35 DA	225	200	8"	45	23	290-298,5	200	314	71	145	40	9	175	395	246	138	87,5	65,5	591

